

APUTURE INFINIMAT 1X4 SPECIFICATIONS

CCT: 2,000K – 10,000K

CRI: 96+

TLCI: 97+

CQS (5600K) / CQS (3200K): 95 / 97

SSI (D56) / SSI (D32): 74 / 84

TM-30 RF (Average) / RG (Average): 93 / 100

Max Power Consumption: 201 W

Max Power Output: 162 W

Weather Resistance Rating: IP65

Pixel Count / Pixel Module: 2 pixels / 1x2

Softbox Inflation Time (Air Pump Mini): 28 sec

Softbox Inflation Time (Air Pump Max): 3 sec

Full-Inflation Duration: 7 days

Operating Temperature: -20°C ~ 50°C

Storage Temperature: -20°C ~ 85°C

Control Methods: On-Board, Sidus Link and Sidus Link Pro Apps, DMX/RDM, CRMX, sACN/Art-Net

Firmware Upgradeable: Sidus Link and Sidus Link Pro Apps, USB-A Drive

Wireless Range (Bluetooth & CRMX): ≤100m / ≤328.1ft

Control Box Type: INFINIMAT Control Box 400W (100-240 VAC, 5 A max)

Weight

INFINIMAT 1x4: 2.40kg / 5.29 lbs

Inflatable Softbox 1x4: 0.86kg / 1.90 lbs

Light Control Skirt 1x4: 0.78kg / 1.72 lbs

Light Control Grid 1x4: 0.71kg / 1.56 lbs

Carrying Case: 4.00kg / 8.82 lbs

Dimensions

INFINIMAT 1x4: 124.00 x 34.00cm / 4.07 x 1.12 ft

Inflatable Softbox 1x4: 124.00 x 34.00 x 17.00cm / 4.07 x 1.12 x 0.56 ft

Light Control Skirt 1x4: 300.00 x 50.00cm / 118.00 x 19.69 in

Light Control Grid 1x4: 122.00 x 35.00cm / 4.00 x 1.14 ft

Carrying Case: 76.50 x 47.00 x 26.00cm / 30.11 x 18.50 x 10.23 in

Photometrics

CCT	Dis.	No Modifier	Inflatable Softbox	Softbox + Control Grid
2,000K	1m	4,400 lux / 409 fc	3,540 lux / 329 fc	2,910 lux / 271 fc
	3m	714 lux / 66 fc	416 lux / 39 fc	373 lux / 35 fc
3,200K	1m	5,400 lux / 502 fc	4,310 lux / 401 fc	3,510 lux / 326 fc
	3m	855 lux / 80 fc	514 lux / 48 fc	449 lux / 42 fc
4,300K	1m	5,720 lux / 532 fc	4,560 lux / 424 fc	3,590 lux / 334 fc
	3m	906 lux / 84 fc	547 lux / 51 fc	466 lux / 43 fc
5,600K	1m	6,140 lux / 571 fc	4,900 lux / 456 fc	3,870 lux / 360 fc
	3m	972 lux / 90 fc	586 lux / 54 fc	494 lux / 46 fc
6,500K	1m	6,090 lux / 566 fc	4,870 lux / 453 fc	3,840 lux / 357 fc
	3m	960 lux / 89 fc	582 lux / 54 fc	490 lux / 46 fc
10,000K	1m	5,530 lux / 514 fc	4,440 lux / 413 fc	3,460 lux / 322 fc
	3m	874 lux / 81 fc	531 lux / 49 fc	442 lux / 41 fc